



The Impact X is an intrinsically safe smartphone that has been designed for use in a potentially explosive atmosphere. The tough, waterproof and light aluminium enclosure makes it a versatile smartphone. It also has double the battery life (3000 mpA), can be operated while wearing gloves, and the display can be read in direct sunlight. The Impact X comes with $FlipScape^{TM}$, a novel application which always records videos correctly, irrespective of which way the camera is held. This is because the Impact X automatically switches to a second camera that is at a 90° angle to the standard camera. This means you can record in landscape mode using one hand, leaving the other hand free. The SIPIDO telepresence app is also included, enabling the user to stream live HD videos wherever needed. In this way it is possible to include users in the field in video conferences The Impact X runs on the Android OS. Android is currently the leading operating system for mobile devices. Android guarantees access to the most diverse media with intuitive navigation. The operating system is fast, well-known and can be customised. It is easily updated to new versions.

Explosion protection

Marking ATEX	€ II 2G Ex ib op is IIC T4 Gb	
Certification	Sira 13ATEX5134X	
Marking IECEx	Ex ib op is IIC T4 Gb	
Certification	SIR 13.0047 X	
Marking CSA	Class I, Ex ib IIC T4 Gb Class I, AEx ib IIC T4 Gb	
Certification	CSA file: 70009910	

Technical data

Temperature range	
Operating temperature	-20 °C to +45 °C
Storage temperature	-40 °C to +60 °C
Video and imaging	
Video quality	Full HD video (1080p, 30 fps)
Resolution	8 megapixel stills
Image capture	Dedicated camera button
Video codecs	H.264/AVC
Zoom	4 x
Memory	32 GB

Robust design		
Impact	Impact-resistant to 2 joules	
Drop	Drop-resistant to 2 metres	
Protection class	Waterproof (IP 68)	
Enclosure	Made from one piece of aluminium	
Connections	Covered USB port	
Screen	2 mm Gorilla Glass	
Audio		
Microphone	Digital omnidirectional microphone	
Audio	Full duplex audio communication	
Video recording	Stereo microphones on back	
Headset	Handsfree support	
Wireless headset	Bluetooth audio headset support	
Handsfree	Integrated mic and speaker	
Audio codec	CD quality AAC LD	
Sound quality	Echo cancellation	
Audio out	Standard 3.5 mm connection	
Sensors		
Orientation	3 axis gyroscope	
Positioning	Global Positioning System (GPS)	
Acceleration	Accellerometer	
Navigation	Compass	
Temperature	Sensor	
Pressure	Sensor	
Power supply		
Battery	3000 mAh	
Talk time	8 h	
Video recording	4 h full operating time	
Scope of delivery		
Charger	USB	
Warranty	1 year hardware warranty	
User Manual	Quick guide	
USB cable	USB cable for charging and data transfer	
Software updates	Available using Collaborate Suite	
Packaging	With customised foam inlays	



Size and weight	
Size	150 mm x 65 mm x 12 mm
Weight	290 g (10 oz)
Display and touchscreen	
Screen size	4.3" Retina display
Resolution	480 x 800 pixels
Brightness	Display can be read in direct sunlight
Touchscreen	Suitable for use when wearing gloves
Glass	Gorilla Glass (IP 68)
Buttons	On/Off, Volume, Camera, Android
Applications	
HD Video conference	SIPID0
Management Solution	Collaboration Suite
Browser	HTML5 with full range of features
Document display	PDF and Office documents
ERP	Compatible with ERP systems
Apps	Google Play, Dropbox [™] , Picasa [™] , Flickr [™]
Ergonomics	
Image capture	Flipscape™: Take videos using one hand
Dirt protection	Anti smuge recess for camera glass and screen
Touchscreen	Suitable for use when wearing gloves, moisture resistant
Shape factor	User-friendly due to ergonomic design
Fall protection	Strap for ergonomic operation

Network functions	
Wi-Fi	802.11 a/b/g/n (2.4 GHz & 5 GHz)
Cellular	4G/HSPA+ (CDMA available)
Bluetooth	Bluetooth 4.0
Video Conferencing	Skype, SIP, H.323
Streaming	ISMA, RTSP, HTML5, WebRTC
Network	Firewall traversal technology STUN server support
Bandwidth	Dynamic Bandwidth Control
QoS	Diffserv, IP precedence (QoS)
Operating system	
Android	5.1.1 Lollipop

Ordering information

Impact X for Europe	17-S123-111211110000
Impact X for US	17-S123-111211120000
Impact X for Australia	17-S123-111211130000
Impact X for UK	17-S123-111211140000

Technical data subject to change without notice.